

Scotch®

Super 33+ Vinyl Electrical Tape for Insulating and More

MRO
Essentials

*The professional's choice for
electrical maintenance and repair*

Scotch Super 33+ Vinyl Tape is a maintenance and repair essential because of versatility and more.

- Versatile performance for every MRO electrical job
- Aggressive pressure-sensitive rubber-based adhesive gives a fast, sure grab
- Super stretchy and flexible PVC backing conforms readily to irregular surfaces
- Goes on smoothly at temperatures as low as 0°F (-18°C) and seals safely up to 220°F (105°C)
- Resists hot, cold, and wet weather as well as UV sunlight exposure

- Resists abrasion, acids, alkalis, and copper corrosion for durability
- Flame retardant
- UL Listed and CSA certified

Applications

- Primary electrical insulation for all wire and cable splices up to 600 V and 220°F (105°C)
- Primary electrical insulation for 600 V bus applications, and protective jacketing for low and high voltage bus
- Protective jacketing for high voltage cable splices and repairs
- Wire and cable harnesses
- Primary electrical insulation and sealing for motor lead connections



3M™ Super 33+ Vinyl Electrical Tape

Product	UPC 00-054007-	Size	Case Qty
Super 33+	06130-4	3/4" x 20'	100
	10075-1	3/4" x 44'	100
	06132-8	3/4" x 66'	100
Super 33+ Tape with Dispenser	10216-8	3/4" x 66'	100

MRO Essentials – You could browse through the thousands of products at 3M to find time and work saving solutions for MRO tasks and problems. Or you could make one call to **1-800-362-3550** or go to the one site that focuses specifically on your needs. From abrasives to adhesives, masking tape to ear plugs, electrical connectors to cleaning products, simply click...

www.3M.com/industrial

Product Use: All statements, technical information and recommendations contained in this document are based upon tests or experience that 3M believes are reliable. However, many factors beyond 3M's control can affect the use and performance of a 3M product in a particular application, including the conditions under which the product is used and the time and environmental conditions in which the product is expected to perform. Since these factors are uniquely within the user's knowledge and control, it is essential that the user evaluate the 3M product to determine whether it is fit for a particular purpose and suitable for the user's method of application.

Warranty and Limited Remedy: Unless stated otherwise in 3M's product literature, packaging inserts or product packaging for individual products, 3M warrants that each 3M product meets the applicable specifications at the time 3M ships the product. Individual products may have additional or different warranties as stated on product literature, package inserts or product packages. **3M MAKES NO OTHER WARRANTIES, EXPRESS OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE OR ANY IMPLIED WARRANTY ARISING OUT OF A COURSE OF DEALING, CUSTOM OR USAGE OF TRADE.** User is responsible for determining whether the 3M product is fit for a particular purpose and suitable for user's application. If the 3M product is defective within the warranty period, your exclusive remedy and 3M's and seller's sole obligation will be, at 3M's option, to replace the product or refund the purchase price.

Limitation of Liability: Except where prohibited by law, 3M and seller will not be liable for any loss or damage arising from the 3M product, whether direct, indirect, special, incidental or consequential, regardless of the legal theory asserted, including warranty, contract, negligence or strict liability.



Electrical Markets Division

6801 River Place Blvd
Austin, TX 78726
1-800-245-3573
www.3m.com/electrical



Minimum 10% Post-Consumable Fiber

Scotch and 3M are trademarks of 3M

Printed in U.S.A.
© 3M 2004 78-6901-2172-4